



Sterilization & Life Science Solutions

LABSCI

Laboratory Steam
Sterilizers Series



Laboratory

Tuttnauer, a global sterilization solution expert, is proud to present its LabSci sterilizer series - robust reliable and cost-effective laboratory sterilization solutions for all your lab needs.



Service

Sterilization in a laboratory environment has its unique requirements. Tuttnauer laboratory autoclave sterilizers are designed to provide high quality repeatable performance and accountability for a wide range of lab applications, including: liquids, media, glassware, instruments, clothing, waste, media clothing and laboratory items.



flexibility

LabSci line series offers a wide range of models and sizes from compact benchtop machines to vertical and horizontal sterilizers. Our models include electronically controlled sterilizers, pre-post vacuum technology, innovative control system and much more.



Experience

All our models comply with the highest manufacturing and safety standards, and provided with a built-in printer for GLP-compliant documentation.



Quality

Our sterilizers are backed with full tech and consulting services support to ensure trouble free sterilizing performance.



Tuttnauer LabSci sterilizer series

Choosing the right steam autoclave depends on several considerations: the type of loads, frequency of use, available services and load volumes. The Tuttnauer LabSci autoclave series successfully meets the challenges posed by sterilization in laboratories and research institutes.

Tabletop 19 Liter - 85 Liters		LabSci 9	LabSci 10	LabSci 12	LabSci 15	
Advantages	<ul style="list-style-type: none"> Easy to install Simple to operate Saves Space No Plumbing Required Fast Processing Ideal for small research labs 	✓	✓	✓	✓	 TOOLS/ INSTRUMENTS  GLASS  TEXTILES/CLOTHES
Description	<ul style="list-style-type: none"> Electronic, 4 cycles, Custom cycles available Single button Cycles are fully automated 	✓	✓	✓	✓	
Tabletop 19 Liter - 85 Liters		LabSci 11L	LabSci 15L	LabSci 15L+		
Advantages	<ul style="list-style-type: none"> Easy to install Simple to operate Saves Space No Plumbing Required Fast Processing Complete drying Ideal for small-medium research labs 	✓	✓	✓	 TOOLS/ INSTRUMENTS  GLASS	
Description	<ul style="list-style-type: none"> 16 custom cycles Cycles are fully automated 2 Integrated Temperature probes Four validated cycles (glass, plastic, liquid A and liquid B-waste) 	✓	✓	✓		
Vertical Laboratory Autoclaves 25 Liter, 85 Liters				LabSci 11L-V	LabSci 15L-V	
Advantages	<ul style="list-style-type: none"> Easy to install Simple to operate No Plumbing Required Perfect for Large horizontal objects like Bioreactors 	✓	✓	✓	 TEXTILES/ CLOTHES  LIQUIDS  MEDIA/PLASTIC	
Description	<ul style="list-style-type: none"> Two integrated temp probes Four validated cycles (glass, plastic, liquid A and liquid B-waste) Create up to 16 custom cycles 	✓	✓	✓		
Pre & Post Vacuum Laboratory Autoclave 28 Liter, 85 Liters				LabSci 11L-PVGC		
Advantages	<ul style="list-style-type: none"> Plug and Play Mobile (on wheels) No plumbing required Water saving system Fast processing Complete drying 	✓	-	✓	-	-
Description	<ul style="list-style-type: none"> Pre and Post Vacuum Steam generator Vacuum pump 	✓	✓	✓	✓	✓

All of our sterilizers incorporate advanced technological features to provide safe and validated sterilization:

- All liquid capable sterilizers include temp probes preventing boil-over and ensuring proper sterilization
- Customizable cycles (could be saved on the system and not re-entered each time).
- Options that are available on all "LabSci" models include: Warming (95° to 104°C), Isothermal (80° to 94°C), F₀, 21 CFR with R.P.C.R software and Biohazard filter.



LabSci 9-19 Liter ■ LabSci 10-23 Liter

Automatic LabSci benchtop autoclaves



Tools/
Instruments



Glass



Textiles/
Clothes

2 Year warranty | Free internal printer

**Designed to autoclave wrapped, unwrapped, glass and tools.
Not suitable for liquids.
Sterilization time up to 99 minutes.**

- Temperature selection from 105° to 137°C (221° to 279°F)
- Includes trays
- In-line particle filter to protect valves
- Electronic pressure and temperature sensors
- Low Water Alarm - sounds when reservoir needs to be refilled.
- Standby Heating - keeps chamber warm for quicker cycles
- Built In Printer - Provides a printed summary at the end of each cycle, documenting temperature, elapsed sterilization and drying time, selected cycle number, real time and date, as well as any errors or interruptions that may occur during the cycle.

	LabSci 9	LabSci 10	LabSci 12	LabSci 15
Chamber Volume (L)	19	23	34.4	65
Max Available Height (in)	6.75"	8.3"	10.1"	12.1"
Chamber Dimension (in)	9" x 18"	10" x 18"	12.2" x 18.5"	15" x 20"
External Dimension (in)	20" x 15" x 20"	20" x 15" x 20"	23.5" x 18" x 21.5"	26" x 21" x 27"
Power	120V	120V	230V, 1 phase (60 Hz NEMA 6-15) 	230V, 1 phase (60 Hz NEMA 6-15) 
Utilities	No Plumbing Required	No Plumbing Required	No Plumbing Required	No Plumbing Required
Stainless Steel Stand	N/A	N/A	N/A	FREE With Autoclave





LabSci tabletop autoclaves



LabSci 11L-28 Liter ■ LabSci 15L-65 Liter ■ LabSci-15L+ -85 Liter

2 Year warranty | Free internal printer

Designed to autoclave everything in your lab, including liquids.

- No water utility connections needed, just plug in and add water.
- Two integrated temperature probes for complete sterilization of liquids
- Four validated cycles (glass, plastic, liquid A and liquid B-waste).
- Stores up to 200 past cycles you can open on your PC
- Create up to 16 custom cycles
- Trays Included
- Optional Biohazard filter (BH) prevents contaminated air from exhausting into the lab

Options that are available on all "LabSci" models include: Warming (95° to 104°C), Isothermal (80° to 94°C) F₀, 21 CFR with R.P.C.R software and Biohazard filter.

	LabSci 11L	LabSci 15L	LabSci 15L+
Chamber Volume (L)	28	65	85
Max Available Height (in)	9"	12.1"	12.1"
Chamber Dimension (in) (Øxd)	11" x 18"	15" x 19.7"	15" x 27.2"
External Dimensions (in) (wxhxd)	20.9" x 17.3" x 24.8"	28.3" x 21.3" x 30.1"	28.3" x 21.3" x 37"
Power	230V, 1 phase (60 Hz) NEMA 6-15 	230V, 1 phase (60 Hz) NEMA 6-15 	230V, 3 phase (60 Hz) NEMA L15-30 
Utilities	No plumbing required	No Plumbing Required	No plumbing required
Stainless Steel Stand	N/A	Free with Autoclave	Free with Autoclave

Erlenmeyer Flask (ml) Loading Capacity

	250	500	1000	2000	3000	5000
LabSci11L	1x9	1x4	3	0	0	0
LabSci15L	1x17	1x11	1x6	1x3	0	0
LabSci15L+	1x23	1x17	1x10	1x5	0	0

Schott-Duran Flasks (ml) Loading Capacity

	250	500	1000	2000	3000	5000
LabSci11L	1x12	1x9	1x5	0	0	0
LabSci15L	1x27	1x16	1x11	1x6	0	0
LabSci15L+	1x36	1x23	1x18	1x9	0	0

LabSci vertical autoclaves

LabSci 15LV+V-85 Liter



2 Year warranty | Free internal printer



LabSci 11L-V-28 Liter

Designed to autoclave everything in your lab, including liquids.

- No utility connections needed (models 11L-V and 15L+V) just plug in and add water
- Two integrated temp. probes to ensure the liquid is completely sterilized
- Four validated cycles (glass, plastic, liquid A and liquid B-waste)
- Stores up to 200 past cycles you can open on your PC
- Create up to 16 custom cycles
- Two baskets included
- Optional biohazard filter (BH) prevents contaminated air from exhausting into the lab

Options that are available on all "LabSci" models include: Warming (95° to 104°C), Isothermal (80° to 94°C), F₀, 21 CFR with R.P.C.R software and Biohazard filter.

	LabSci 11L-V	LabSci 15L+V
Chamber Volume (L)	28	85
Max Available Height (in)	15.5"	25"
Chamber Dimensions (in) (Øxd)	11" x 18"	15" x 27.2"
External Dimensions (in) (wxhxd)	21.3" x 39" x 17.3"	29" x 42" x 29"
Power	230V, 1 phase (60 Hz) NEMA 6-15 	230V, 3 phase (60 Hz) NEMA L15-30 
Utilities	No plumbing required	No plumbing required

Erlenmeyer Flask (ml) Loading Capacity

	250	500	1000	2000	3000	5000
LabSci11L-V	2 x 5	2 x 3	1	1	1	1
LabSci15L+V	3 x 12	3 x 8	2 x 5	2 x 2	2 x 1	1

Schott-Duran Flasks (ml) Loading Capacity

	250	500	1000	2000	3000	5000
LABSCI11L-V	2 x 8	2 x 3	1	1	1	1
LABSCI15L+V	3 x 19	3 x 12	2 x 8	2 x 2	2 x 1	1

LabSci 11L-PVGC autoclaves



2 Year warranty | Free internal printer



LabSci 11L-PVGC - 28 Liter

LabSci Autoclaves with Cooling Coils "C", Vacuum Pump "PV" and an integrated steam generator "G"

- Steam generator for heat on demand and quicker heat up times.
- Pre & Post Vacuum for faster more efficient air removal (tubing, glassware, pouches, wrapped tools or garments)
- Cooling Coils decreases cool down time by 75%
- Steam generator with post vacuum for complete drying
- Optional Biohazard filter (BH) prevents contaminated air from exhausting into the lab

Options that are available on all "LabSci" models include: Warming (95° to 104°C), Isothermal (80° to 94°C), F₀, 21 CFR with R.P.C.R software and Biohazard filter..


	LabSci 11L-PVGC
Chamber Volume (L)	28
Max Available Height (in)	9"
Chamber Dimension (in)	11" x 18"
External Dimension (in)	20.9" x 17.3" x 29.9"
Power	230v, 1 PHASE (60 Hz) NEMA 6-15 
Utilities	Treated Water, Tap Water, Compressed Air and Floor Sink

Erlenmeyer Flask (ml) Loading Capacity

	250	500	1000	2000	3000	5000
LabSci 11L-PVGC	1 x 9	1 x 4	3	0	0	0

Schott-Duran Flasks (ml) Loading Capacity

	250	500	1000	2000	3000	5000
LabSci 11L-PVGC	1 x 12	1 x 9	1 x 5	0	-	0



Tuttnauer Autoclaves - Service By Heidolph

Tuttnauer, partnered with Heidolph to provide all service. Tuttnauer sterilizers require general maintenance and cleaning. A sterilizer often requires regulatory compliance at some local, or federal standard based on the application within the operation of the unit. Our factory trained technicians are here to provide basic product upkeep, and to support your sterilizer through a variety of services outlined below:

Preventive Maintenance (with or without calibration recommended yearly on-site or in-house)

- Replacement of Chamber Brite, safety valve, safety valve holder, door bellow, door gasket, clean water electrode, strainer, and inspect the reservoir and piping
- Solenoid Valves are checked for proper operation
- Safety features are tested
- Preventive maintenance agreements come with discount on parts

PM with calibration

- Everything included with the PM service, plus temperature and pressure calibration with empty chamber temperature mapping
- A total of three cycles with probes will be run

IQ/OQ (recommended)

- Documented proof that facilities and equipment have been delivered and installed, in accordance with the requirements and safety regulations stipulated in the design qualifications
- Consists of:
IQ/OQ test plan and report
Temperature and pressure mapping

IQ/OQ/PQ

- Documented proof that utilities and equipment have been delivered and installed, in accordance with the requirements and safety regulations stipulated in the design qualifications
- Consists of:
- IQ/OQ/PQ all testing and reports in the IQ/OQ plus a half and full load cycle tests
- Please contact Heidolph to discuss your PQ needs to structure the load testing to meet your application



Learn from our experts.

Visit our blog: tuttnauerusa.com/blog

Tuttnauer USA Co. Ltd.

25 Power Drive, Hauppauge, NY 11788

Tel: +800 624 5836, +631 737 4850, Fax: +631 737 0720

E-mail: info@tuttnauerUSA.com, www.tuttnauerUSA.com



Heidolph North America

1235 Mittle Blvd., Suite B, Wood Dale, IL 60191

Tel: +800 265-9600

E-mail: hello@heidolph.com, www.HeidolphNA.com